Clear Choice®

APPLICATION TAPE
CLEAR

NEKOOSA.COM



The universal clear application tape for maximum versatility and precision.

Clear Choice® is an ultra-clear application tape that provides exceptional performance and versatility for the widest range of sign applications.

AT60n Low Tack

Embossed film for transferring large cut graphics and protecting digital prints. Fine Texture for easy release/unwind and installation.

AT65 High Tack

Embossed film for transferring small and fine detail cut graphics and vinyl films with tight release liners. Fine Texture for easy release/unwind and installation.

AT75.1 High Tack

Embossed surface film ideal for small to medium size cut graphics with heavy texture air-egress micro channels for bubble-free lamination of tape to film.

New! Product Improvements

- Enhanced adhesion
- Improved release liner adhesion with Conform® characteristics
- Improvements to lifting and transferring graphics
- No adhesive residue with wet applications
- No water whitening upon contact with water/solution

Applications

Textured & Matte Finish Vinyl Films

Fine Lettering

Textured Wrap, Window, & Wall Films

Thermal Die Cuts

Product Information

Clear film

Repositionable

Easy handling and removal

No milky residue and water whitening when used for wet applications

r.tape
A NEKOOSA BRAND

NEKOOSA

N. America: 800.440.1250 | sales@rtape.com
Europe: +32 9 216 6700 | info@theicgroup.eu


02.21.19 | M1198

Clear Choice®

APPLICATION TAPE
CLEAR

NEKOOSA.COM





AT75.1 vs AT60n ▼ *See the difference!*



TECHNICAL DATA

Physical Properties		AT60n	AT65	AT75.1
Color Transparent	**Adhesive**	Acrylic	Acrylic	Modified polyacrylate
Shelf Life 1 Year	**Caliper**	Embossed Polypropylene	Embossed Polypropylene	Embossed HOPE
		3.7 mil (93 µ)	3.7 mil (93.7 µ)	4.25 mil (106.4 µ)
	Tack Level	Low	HIgh	High
	Adhesion to Steel*	1-4 N/100 mm (1-3 oz.)	2.1-6.5 N/100 mm (2 - 6 oz.)	2.1 N/25 mm (7.5 oz.)
	Die-Cut Graphics Size	Large	Small-Med	Small-Med
	Wet Application Installation	Good	Excellent	Excellent
	Compatible Vinyl	Gloss/Smooth	Gloss/Smooth	Gloss/Smooth and Matte/Textured Vinyl
	Tensile	25 MPa (3600 psi)	25 MPa (3600 psi)	13 MPa (2000 psi)
	Elongation	750%	750%	300-500%

*** TEST METHOD:** PSTC-101



WARRANTY Tapes are only warranted to be free of defects in workmanship or materials at time of shipment. Nekoosa will replace or credit any material deemed to be defective. No acceptance or responsibility for loss, damage, or expense, implied or otherwise, shall be assumed by the seller or manufacturer. The end user assumes all risk and liability.

Digital Coated 80# cover • Ricoh Pro C7100SX

N. America: 800.440.1250 | sales@rtape.com
Europe: +32 9 216 6700 | info@theicgroup.eu