Conform®

APPLICATION TAPE
WITH RLA

NEKOOSA.COM



Always lays flat, with no edge curling, wrinkling, or tunneling.

Conform® is the original application tape with RLA® Release Liner Adhesion. With RLA, Conform sticks to slick release liners, so tapes do not "dog ear" and stick together. Graphics stay neater and cleaner, even when they're rolled.

4075RLA High Tack *Most popular!*

Standard weight paper application tape with a high tack rubber adhesive. Perfect for small to mid-sized pre-spaced vinyls and printed graphics.

4076RLA Very High Tack

Standard weight paper application tape, coated with a slightly higher tack rubber adhesive. Perfect for small-sized cut graphics and hard-to-lift vinyls.

4050RLA Medium Tack

Standard weight paper application tape with a medium tack rubber adhesive. Perfect for medium to large-sized, prespaced vinyl and printed graphics.

4078RLA Medium Tack

Standard weight paper application tape with a medium tack rubber adhesive. Recommended for applying wall graphics, textured and frosted vinyl.

Applications

- General Purpose Sign Applications
- Decals
- Banners
- Wall Graphics

Product Information

- RLA® Release Liner Adhesion
- Lays flat with no tunneling or edge curling
- Factory cut, razor slit rolls
- No adhesive balls, gapping between layers or crushed edges
- Tears cleanly – no stringy, legging adhesive
- Multiple roll widths available
- No adhesive build-up on stored graphics
- Works in either wet or dry applications

r.tape
A NEKOOSA BRAND
NEKOOSA

N. America: 800.440.1250 | sales@rtape.com
Europe: +32 9 216 6700 | info@theicgroup.eu

02.15.19 | M1199

Conform®

APPLICATION TAPE
WITH RLA

NEKOOSA.COM








TECHNICAL DATA

Physical Properties	
Adhesive	Rubber-Based
Color	Off White/Translucent
Tensile	297 N/100 mm (17lb/in)
Elongation	3-4%
Tear Resistance	50
Shelf Life	1 Year

		4078RLA	4050RLA	4075RLA	4076RLA
Caliper	Facestock	3.0 mil	3.0 mil	3.0 mil	3.0 mil
	Facestock + Adhesive	4.1 mil	4.2 mil	4.2 mil	4.3 mil
Tack Level		Medium	Medium	High	Very High Tack
Adhesion to Steel*		9 - 11 N/100 mm (7.5 - 8 oz)	13 - 15 N/100 mm (12 - 14 oz)	18 - 20 N/100 mm (16 - 18 oz)	19 - 21 N/100 mm (17 - 19 oz)

*** TEST METHOD:** PSTC-101



WARRANTY Tapes are only warranted to be free of defects in workmanship or materials at time of shipment. Nekoosa will replace or credit any material deemed to be defective. No acceptance or responsibility for loss, damage, or expense, implied or otherwise, shall be assumed by the seller or manufacturer. The end user assumes all risk and liability.

Digital Coated 80# cover • Ricoh Pro C7100SX

N. America: 800.440.1250 | sales@rtape.com
Europe: +32 9 216 6700 | info@theicgroup.eu